

Bezeichnung	Artikelnummer	Lichtfarbe	Optik	Systemleistung	Lichtstrom System	Abmessungen
BaseLED 10-585 M1K	96009403015	4000 K	satiniert	10,1 W	1333 lm	585x74x32 mm
BaseLED 15-865 K1K	96013303006	3000 K	klar	13,4 W	2081 lm	865x74x35 mm
BaseLED 15-865 M1K	96013303007	3000 K	klar	13,4 W	2081 lm	865x74x32 mm
BaseLED 15-865 K1K	96013303014	3000 K	satiniert	13,4 W	1888 lm	865x74x35 mm
BaseLED 15-865 M1K	96013303015	3000 K	satiniert	13,4 W	1888 lm	865x74x32 mm
BaseLED 15-865 D1K	96013303018	3000 K	klar	13,4 W	2081 lm	865x74x34 mm
BaseLED 15-865 D1K	96013303019	3000 K	satiniert	13,4 W	1888 lm	865x74x34 mm
BaseLED 15-865 K1K	96013403006	4000 K	klar	13,4 W	2207 lm	865x74x35 mm
BaseLED 15-865 M1K	96013403007	4000 K	klar	13,4 W	2207 lm	865x74x32 mm
BaseLED 15-865 K1K	96013403014	4000 K	satiniert	13,4 W	2002 lm	865x74x35 mm
BaseLED 15-865 M1K	96013403015	4000 K	satiniert	13,4 W	2002 lm	865x74x32 mm
BaseLED 15-865 D1K	96013403018	4000 K	klar	13,4 W	2207 lm	865x74x34 mm
BaseLED 15-865 D1K	96013403019	4000 K	satiniert	13,4 W	2002 lm	865x74x34 mm
BaseLED 15-865 K1K	96013503006	5000 K	klar	13,8 W	2095 lm	865x74x35 mm
BaseLED 15-865 M1K	96013503007	5000 K	klar	13,8 W	2095 lm	865x74x32 mm
BaseLED 15-865 K1K	96013503014	5000 K	satiniert	13,8 W	1901 lm	865x74x35 mm
BaseLED 15-865 M1K	96013503015	5000 K	satiniert	13,8 W	1901 lm	865x74x32 mm
BaseLED 15-865 D1K	96013503018	5000 K	klar	13,8 W	2095 lm	865x74x34 mm
BaseLED 15-865 D1K	96013503019	5000 K	satiniert	13,8 W	1901 lm	865x74x34 mm
BaseLED 15-865 M1K	96013653015	6500 K	satiniert	13,4 W	1861 lm	865x74x32 mm
BaseLED 19-1145 K1K	96017303006	3000 K	klar	17,2 W	2774 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017303007	3000 K	klar	17,2 W	2774 lm	1145x74x32 mm
BaseLED 19-1145 K1K	96017303014	3000 K	satiniert	17,2 W	2517 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017303015	3000 K	satiniert	17,2 W	2517 lm	1145x74x32 mm
BaseLED 19-1145 D1K	96017303018	3000 K	klar	17,2 W	2774 lm	1145x74x34 mm
BaseLED 19-1145 D1K	96017303019	3000 K	satiniert	17,2 W	2517 lm	1145x74x34 mm
BaseLED 19-1145 K1K	96017403006	4000 K	klar	17,2 W	2939 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017403007	4000 K	klar	17,2 W	2939 lm	1145x74x32 mm
BaseLED 19-1145 K1K	96017403014	4000 K	satiniert	17,2 W	2666 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017403015	4000 K	satiniert	17,2 W	2666 lm	1145x74x32 mm
BaseLED 19-1145 D1K	96017403018	4000 K	klar	17,2 W	2939 lm	1145x74x34 mm
BaseLED 19-1145 D1K	96017403019	4000 K	satiniert	17,2 W	2666 lm	1145x74x34 mm
BaseLED 19-1145 K1K	96017503006	5000 K	klar	17,7 W	2794 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017503007	5000 K	klar	17,7 W	2794 lm	1145x74x32 mm
BaseLED 19-1145 K1K	96017503014	5000 K	satiniert	17,7 W	2534 lm	1145x74x35 mm
BaseLED 19-1145 M1K	96017503015	5000 K	satiniert	17,7 W	2534 lm	1145x74x32 mm
BaseLED 19-1145 D1K	96017503018	5000 K	klar	17,7 W	2794 lm	1145x74x34 mm
BaseLED 19-1145 D1K	96017503019	5000 K	satiniert	17,7 W	2534 lm	1145x74x34 mm
BaseLED 23-1425 K1K	96022303006	3000 K	klar	20,9 W	3468 lm	1425x74x35 mm
BaseLED 23-1425 M1K	96022303007	3000 K	klar	20,9 W	3468 lm	1425x74x32 mm
BaseLED 23-1425 K1K	96022303014	3000 K	satiniert	20,9 W	3146 lm	1425x74x35 mm
BaseLED 23-1425 M1K	96022303015	3000 K	satiniert	20,9 W	3146 lm	1425x74x32 mm
BaseLED 23-1425 D1K	96022303018	3000 K	klar	20,9 W	3468 lm	1425x74x34 mm
BaseLED 23-1425 D1K	96022303019	3000 K	satiniert	20,9 W	3146 lm	1425x74x34 mm
BaseLED 23-1425 K1K	96022403006	4000 K	klar	20,9 W	3676 lm	1425x74x35 mm

BaseLED 23-1425 M1K	96022403007	4000 K	klar	20,9 W	3676 lm	1425x74x32 mm
BaseLED 23-1425 K1K	96022403014	4000 K	satiniert	20,9 W	3335 lm	1425x74x35 mm
BaseLED 23-1425 M1K	96022403015	4000 K	satiniert	20,9 W	3335 lm	1425x74x32 mm
BaseLED 23-1425 D1K	96022403018	4000 K	klar	20,9 W	3676 lm	1425x74x34 mm
BaseLED 23-1425 D1K	96022403019	4000 K	satiniert	20,9 W	3335 lm	1425x74x34 mm
BaseLED 23-1425 K1K	96022503006	5000 K	klar	21,6 W	3492 lm	1425x74x35 mm
BaseLED 23-1425 M1K	96022503007	5000 K	klar	21,6 W	3492 lm	1425x74x32 mm
BaseLED 23-1425 K1K	96022503014	5000 K	satiniert	21,6 W	3168 lm	1425x74x35 mm
BaseLED 23-1425 M1K	96022503015	5000 K	satiniert	21,6 W	3168 lm	1425x74x32 mm
BaseLED 23-1425 D1K	96022503018	5000 K	klar	21,6 W	3492 lm	1425x74x34 mm
BaseLED 23-1425 D1K	96022503019	5000 K	satiniert	21,6 W	3168 lm	1425x74x34 mm