

Bezeichnung	Artikelnummer	Lichtfarbe	Optik	System-leistung
HalLED 16-865 AS	87016303003	3000 K	satiniert	#BEZUG!
HalLED 16-865 AS dim	87016303004	3000 K	satiniert	#BEZUG!
HalLED 16-865 AS	87016303009	3000 K	klar	#BEZUG!
HalLED 16-865 AS dim	87016303010	3000 K	klar	#BEZUG!
HalLED 16-865 AS	87016403003	4000 K	satiniert	#BEZUG!
HalLED 16-865 AS dim	87016403004	4000 K	satiniert	#BEZUG!
HalLED 16-865 AS	87016403009	4000 K	klar	#BEZUG!
HalLED 16-865 AS dim	87016403010	4000 K	klar	#BEZUG!
HalLED 16-865 AS dim	87016503004	5000 K	satiniert	#BEZUG!
HalLED 16-865 AS	87016503009	5000 K	klar	#BEZUG!
HalLED 16-865 AS dim	87016503010	5000 K	klar	#BEZUG!
HalLED 17-1145 AS	87017303003	3000 K	satiniert	19,4 W
HalLED 17-1145 AS dim	87017303004	3000 K	satiniert	19,7 W
HalLED 17-1145 AS	87017303009	3000 K	klar	19,4 W
HalLED 17-1145 AS dim	87017303010	3000 K	klar	19,7 W
HalLED 17-1145 AS	87017403003	4000 K	satiniert	19,4 W
HalLED 17-1145 AS dim	87017403004	4000 K	satiniert	19,7 W
HalLED 17-1145 AS	87017403009	4000 K	klar	19,4 W
HalLED 17-1145 AS dim	87017403010	4000 K	klar	19,7 W
HalLED 17-1145 AS	87017503003	5000 K	satiniert	19,4 W
HalLED 17-1145 AS dim	87017503004	5000 K	satiniert	19,7 W
HalLED 17-1145 AS	87017503009	5000 K	klar	19,4 W
HalLED 17-1145 AS dim	87017503010	5000 K	klar	19,7 W
HalLED 22-1425 AS	87022303003	3000 K	satiniert	23,9 W
HalLED 22-1425 AS dim	87022303004	3000 K	satiniert	24,2 W
HalLED 22-1425 AS	87022303009	3000 K	klar	23,9 W
HalLED 22-1425 AS dim	87022303010	3000 K	klar	24,2 W
HalLED 22-1425 AS	87022403003	4000 K	satiniert	23,9 W
HalLED 22-1425 AS dim	87022403004	4000 K	satiniert	24,2 W
HalLED 22-1425 AS	87022403009	4000 K	klar	23,9 W
HalLED 22-1425 AS dim	87022403010	4000 K	klar	24,2 W
HalLED 22-1425 AS	87022503003	5000 K	satiniert	23,9 W
HalLED 22-1425 AS dim	87022503004	5000 K	satiniert	24,2 W
HalLED 22-1425 AS	87022503009	5000 K	klar	23,9 W
HalLED 22-1425 AS dim	87022503010	5000 K	klar	24,2 W
HalLED 24-865 AS	87024303003	3000 K	satiniert	26,9 W
HalLED 24-865 AS dim	87024303004	3000 K	satiniert	27,2 W
HalLED 24-865 AS	87024303009	3000 K	klar	26,9 W
HalLED 24-865 AS dim	87024303010	3000 K	klar	27,2 W
HalLED 24-865 AS	87024403003	4000 K	satiniert	26,9 W
HalLED 24-865 AS dim	87024403004	4000 K	satiniert	27,2 W
HalLED 24-865 AS	87024403009	4000 K	klar	26,9 W
HalLED 24-865 AS dim	87024403010	4000 K	klar	27,2 W
HalLED 24-865 AS	87024503003	5000 K	satiniert	26,9 W
HalLED 24-865 AS dim	87024503004	5000 K	satiniert	27,2 W
HalLED 24-865 AS	87024503009	5000 K	klar	26,9 W

HalLED 24-865 AS dim	87024503010	5000 K	klar	27,2 W
HalLED 30-1425 AS	87030303003	3000 K	satiniert	30,4 W
HalLED 30-1425 AS dim	87030303004	3000 K	satiniert	30,7 W
HalLED 30-1425 AS	87030303009	3000 K	klar	30,4 W
HalLED 30-1425 AS dim	87030303010	3000 K	klar	30,7 W
HalLED 30-1425 AS	87030403003	4000 K	satiniert	30,4 W
HalLED 30-1425 AS dim	87030403004	4000 K	satiniert	30,7 W
HalLED 30-1425 AS	87030403009	4000 K	klar	30,4 W
HalLED 30-1425 AS dim	87030403010	4000 K	klar	30,7 W
HalLED 30-1425 AS	87030503003	5000 K	satiniert	30,4 W
HalLED 30-1425 AS dim	87030503004	5000 K	satiniert	30,7 W
HalLED 30-1425 AS	87030503009	5000 K	klar	30,4 W
HalLED 30-1425 AS dim	87030503010	5000 K	klar	30,7 W
HalLED 32-1145 AS	87032303003	3000 K	satiniert	34,7 W
HalLED 32-1145 AS dim	87032303004	3000 K	satiniert	35,1 W
HalLED 32-1145 AS	87032303009	3000 K	klar	34,7 W
HalLED 32-1145 AS dim	87032303010	3000 K	klar	35,1 W
HalLED 32-1145 AS	87032403003	4000 K	satiniert	34,7 W
HalLED 32-1145 AS dim	87032403004	4000 K	satiniert	35,1 W
HalLED 32-1145 AS	87032403009	4000 K	klar	34,7 W
HalLED 32-1145 AS dim	87032403010	4000 K	klar	35,1 W
HalLED 32-1145 AS	87032503003	5000 K	satiniert	34,7 W
HalLED 32-1145 AS dim	87032503004	5000 K	satiniert	35,1 W
HalLED 32-1145 AS	87032503009	5000 K	klar	34,7 W
HalLED 32-1145 AS dim	87032503010	5000 K	klar	35,1 W
HalLED 40-1425 AS	87040303003	3000 K	satiniert	42,5 W
HalLED 40-1425 AS dim	87040303004	3000 K	satiniert	42,9 W
HalLED 40-1425 AS	87040303009	3000 K	klar	42,5 W
HalLED 40-1425 AS dim	87040303010	3000 K	klar	42,9 W
HalLED 40-1425 AS	87040403003	4000 K	satiniert	42,5 W
HalLED 40-1425 AS dim	87040403004	4000 K	satiniert	42,9 W
HalLED 40-1425 AS	87040403009	4000 K	klar	42,5 W
HalLED 40-1425 AS dim	87040403010	4000 K	klar	42,9 W
HalLED 40-1425 AS	87040503003	5000 K	satiniert	42,5 W
HalLED 40-1425 AS dim	87040503004	5000 K	satiniert	42,9 W
HalLED 40-1425 AS	87040503009	5000 K	klar	42,5 W
HalLED 40-1425 AS dim	87040503010	5000 K	klar	42,9 W

Lichtstrom System	Abmessungen
2138 lm	865x39x64 mm
2138 lm	865x39x64 mm
2357 lm	865x39x64 mm
2357 lm	865x39x64 mm
2270 lm	865x39x64 mm
2270 lm	865x39x64 mm
2503 lm	865x39x64 mm
2503 lm	865x39x64 mm
2270 lm	865x39x64 mm
2503 lm	865x39x64 mm
2503 lm	865x39x64 mm
2851 lm	1145x39x64 mm
2851 lm	1145x39x64 mm
3143 lm	1145x39x64 mm
3143 lm	1145x39x64 mm
3027 lm	1145x39x64 mm
3027 lm	1145x39x64 mm
3337 lm	1145x39x64 mm
3337 lm	1145x39x64 mm
3027 lm	1145x39x64 mm
3027 lm	1145x39x64 mm
3337 lm	1145x39x64 mm
3337 lm	1145x39x64 mm
3564 lm	1425x39x64 mm
3564 lm	1425x39x64 mm
3929 lm	1425x39x64 mm
3929 lm	1425x39x64 mm
3784 lm	1425x39x64 mm
3784 lm	1425x39x64 mm
4171 lm	1425x39x64 mm
4171 lm	1425x39x64 mm
3784 lm	1425x39x64 mm
3784 lm	1425x39x64 mm
4171 lm	1425x39x64 mm
4171 lm	1425x39x64 mm
3630 lm	865x39x64 mm
3630 lm	865x39x64 mm
4001 lm	865x39x64 mm
4001 lm	865x39x64 mm
3868 lm	865x39x64 mm
3868 lm	865x39x64 mm
4263 lm	865x39x64 mm
4263 lm	865x39x64 mm
3868 lm	865x39x64 mm
3868 lm	865x39x64 mm
4263 lm	865x39x64 mm

4263 lm	865x39x64 mm
4400 lm	1425x39x64 mm
4400 lm	1425x39x64 mm
4850 lm	1425x39x64 mm
4850 lm	1425x39x64 mm
4686 lm	1425x39x64 mm
4686 lm	1425x39x64 mm
5165 lm	1425x39x64 mm
5165 lm	1425x39x64 mm
4686 lm	1425x39x64 mm
4686 lm	1425x39x64 mm
5165 lm	1425x39x64 mm
5165 lm	1425x39x64 mm
4840 lm	1145x39x64 mm
4840 lm	1145x39x64 mm
5335 lm	1145x39x64 mm
5335 lm	1145x39x64 mm
5157 lm	1145x39x64 mm
5157 lm	1145x39x64 mm
5684 lm	1145x39x64 mm
5684 lm	1145x39x64 mm
5157 lm	1145x39x64 mm
5157 lm	1145x39x64 mm
5684 lm	1145x39x64 mm
5684 lm	1145x39x64 mm
6050 lm	1425x39x64 mm
6050 lm	1425x39x64 mm
6669 lm	1425x39x64 mm
6669 lm	1425x39x64 mm
6446 lm	1425x39x64 mm
6446 lm	1425x39x64 mm
7105 lm	1425x39x64 mm
7105 lm	1425x39x64 mm
6446 lm	1425x39x64 mm
6446 lm	1425x39x64 mm
7105 lm	1425x39x64 mm
7105 lm	1425x39x64 mm