

Bezeichnung	Artikelnummer	Abmessungen	Lichtfarbe	Abdeckung	Systemleistung	Lichtstrom System
BaseLED 15-865 KE	96013303002	865x74x35 mm	3000 K	klar	14,9 W	1925 lm
BaseLED 15-865 ME	96013303003	865x74x32 mm	3000 K	klar	14,9 W	1925 lm
BaseLED 15-865 KE	96013303010	865x74x35 mm	3000 K	satiniert	14,9 W	1747 lm
BaseLED 15-865 ME	96013303011	865x74x32 mm	3000 K	satiniert	14,9 W	1747 lm
BaseLED 15-865 DE	96013303020	865x74x34 mm	3000 K	klar	14,9 W	1925 lm
BaseLED 15-865 DE	96013303021	865x74x34 mm	3000 K	satiniert	14,9 W	1747 lm
BaseLED 15-865 KE	96013403002	865x74x35 mm	4000 K	klar	14,9 W	2022 lm
BaseLED 15-865 ME	96013403003	865x74x32 mm	4000 K	klar	14,9 W	2022 lm
BaseLED 15-865 KE	96013403010	865x74x35 mm	4000 K	satiniert	14,9 W	1835 lm
BaseLED 15-865 ME	96013403011	865x74x32 mm	4000 K	satiniert	14,9 W	1835 lm
BaseLED 15-865 DE	96013403020	865x74x34 mm	4000 K	klar	14,9 W	2022 lm
BaseLED 15-865 DE	96013403021	865x74x34 mm	4000 K	satiniert	14,9 W	1835 lm
BaseLED 15-865 KE	96013503002	865x74x35 mm	5000 K	klar	14,9 W	2076 lm
BaseLED 15-865 ME	96013503003	865x74x32 mm	5000 K	klar	14,9 W	2076 lm
BaseLED 15-865 KE	96013503010	865x74x35 mm	5000 K	satiniert	14,9 W	1883 lm
BaseLED 15-865 ME	96013503011	865x74x32 mm	5000 K	satiniert	14,9 W	1883 lm
BaseLED 15-865 DE	96013503020	865x74x34 mm	5000 K	klar	14,9 W	2076 lm
BaseLED 15-865 DE	96013503021	865x74x34 mm	5000 K	satiniert	14,9 W	1883 lm
BaseLED 19-1145 KE	96017303002	1145x74x35 mm	3000 K	klar	18,9 W	2566 lm
BaseLED 19-1145 ME	96017303003	1145x74x32 mm	3000 K	klar	18,9 W	2566 lm
BaseLED 19-1145 KE	96017303010	1145x74x35 mm	3000 K	satiniert	18,9 W	2328 lm
BaseLED 19-1145 ME	96017303011	1145x74x32 mm	3000 K	satiniert	18,9 W	2328 lm
BaseLED 19-1145 DE	96017303020	1145x74x34 mm	3000 K	klar	18,9 W	2566 lm
BaseLED 19-1145 DE	96017303021	1145x74x34 mm	3000 K	satiniert	18,9 W	2328 lm
BaseLED 19-1145 KE	96017403002	1145x74x35 mm	4000 K	klar	18,9 W	2692 lm
BaseLED 19-1145 ME	96017403003	1145x74x32 mm	4000 K	klar	18,9 W	2692 lm
BaseLED 19-1145 KE	96017403010	1145x74x35 mm	4000 K	satiniert	18,9 W	2442 lm
BaseLED 19-1145 ME	96017403011	1145x74x32 mm	4000 K	satiniert	18,9 W	2442 lm
BaseLED 19-1145 DE	96017403020	1145x74x34 mm	4000 K	klar	18,9 W	2692 lm
BaseLED 19-1145 DE	96017403021	1145x74x34 mm	4000 K	satiniert	18,9 W	2442 lm
BaseLED 19-1145 KE	96017503002	1145x74x35 mm	5000 K	klar	18,9 W	2765 lm
BaseLED 19-1145 ME	96017503003	1145x74x32 mm	5000 K	klar	18,9 W	2765 lm
BaseLED 19-1145 KE	96017503010	1145x74x35 mm	5000 K	satiniert	18,9 W	2508 lm
BaseLED 19-1145 ME	96017503011	1145x74x32 mm	5000 K	satiniert	18,9 W	2508 lm
BaseLED 19-1145 DE	96017503020	1145x74x34 mm	5000 K	klar	18,9 W	2765 lm
BaseLED 19-1145 DE	96017503021	1145x74x34 mm	5000 K	satiniert	18,9 W	2508 lm
BaseLED 23-1425 KE	96022303002	1425x74x35 mm	3000 K	klar	23,0 W	3206 lm
BaseLED 23-1425 ME	96022303003	1425x74x32 mm	3000 K	klar	23,0 W	3206 lm
BaseLED 23-1425 KE	96022303010	1425x74x35 mm	3000 K	satiniert	23,0 W	2908 lm
BaseLED 23-1425 ME	96022303011	1425x74x32 mm	3000 K	satiniert	23,0 W	2908 lm
BaseLED 23-1425 DE	96022303020	1425x74x34 mm	3000 K	klar	23,0 W	3206 lm
BaseLED 23-1425 DE	96022303021	1425x74x34 mm	3000 K	satiniert	23,0 W	2908 lm
BaseLED 23-1425 KE	96022403002	1425x74x35 mm	4000 K	klar	23,0 W	3366 lm
BaseLED 23-1425 ME	96022403003	1425x74x32 mm	4000 K	klar	23,0 W	3366 lm
BaseLED 23-1425 KE	96022403010	1425x74x35 mm	4000 K	satiniert	23,0 W	3054 lm
BaseLED 23-1425 ME	96022403011	1425x74x32 mm	4000 K	satiniert	23,0 W	3054 lm
BaseLED 23-1425 DE	96022403020	1425x74x34 mm	4000 K	klar	23,0 W	3366 lm
BaseLED 23-1425 DE	96022403021	1425x74x34 mm	4000 K	satiniert	23,0 W	3054 lm
BaseLED 23-1425 KE	96022503002	1425x74x35 mm	5000 K	klar	23,0 W	3458 lm
BaseLED 23-1425 ME	96022503003	1425x74x32 mm	5000 K	klar	23,0 W	3458 lm
BaseLED 23-1425 KE	96022503010	1425x74x35 mm	5000 K	satiniert	23,0 W	3137 lm
BaseLED 23-1425 ME	96022503011	1425x74x32 mm	5000 K	satiniert	23,0 W	3137 lm
BaseLED 23-1425 DE	96022503020	1425x74x34 mm	5000 K	klar	23,0 W	3458 lm
BaseLED 23-1425 DE	96022503021	1425x74x34 mm	5000 K	satiniert	23,0 W	3137 lm