

Bezeichnung	Artikelnummer	Abmessungen	Lichtfarbe	Abdeckung	Systemleistung	Lichtstrom System
HaILED 16-865 AS	87016303003	865x39x64 mm	3000 K	satiniert	15,3 W	1993 lm
HaILED 16-865 AS dim	87016303004	865x39x64 mm	3000 K	satiniert	15,5 W	1993 lm
HaILED 16-865 AS	87016303009	865x39x64 mm	3000 K	klar	15,3 W	2197 lm
HaILED 16-865 AS dim	87016303010	865x39x64 mm	3000 K	klar	15,5 W	2197 lm
HaILED 16-865 AS	87016403003	865x39x64 mm	4000 K	satiniert	15,3 W	2152 lm
HaILED 16-865 AS dim	87016403004	865x39x64 mm	4000 K	satiniert	15,5 W	2152 lm
HaILED 16-865 AS	87016403009	865x39x64 mm	4000 K	klar	15,3 W	2372 lm
HaILED 16-865 AS dim	87016403010	865x39x64 mm	4000 K	klar	15,5 W	2372 lm
HaILED 16-865 AS	87016503003	865x39x64 mm	5000 K	satiniert	15,3 W	2178 lm
HaILED 16-865 AS dim	87016503004	865x39x64 mm	5000 K	satiniert	15,5 W	2178 lm
HaILED 16-865 AS	87016503009	865x39x64 mm	5000 K	klar	15,3 W	2401 lm
HaILED 16-865 AS dim	87016503010	865x39x64 mm	5000 K	klar	15,5 W	2401 lm
HaILED 17-1145 AS	87017303003	1145x39x64 mm	3000 K	satiniert	19,8 W	2675 lm
HaILED 17-1145 AS dim	87017303004	1145x39x64 mm	3000 K	satiniert	20,0 W	2675 lm
HaILED 17-1145 AS	87017303009	1145x39x64 mm	3000 K	klar	19,8 W	2949 lm
HaILED 17-1145 AS dim	87017303010	1145x39x64 mm	3000 K	klar	20,0 W	2949 lm
HaILED 17-1145 AS	87017403003	1145x39x64 mm	4000 K	satiniert	19,8 W	2886 lm
HaILED 17-1145 AS dim	87017403004	1145x39x64 mm	4000 K	satiniert	20,0 W	2886 lm
HaILED 17-1145 AS	87017403009	1145x39x64 mm	4000 K	klar	19,8 W	3182 lm
HaILED 17-1145 AS dim	87017403010	1145x39x64 mm	4000 K	klar	20,0 W	3182 lm
HaILED 17-1145 AS	87017503003	1145x39x64 mm	5000 K	satiniert	19,8 W	2922 lm
HaILED 17-1145 AS dim	87017503004	1145x39x64 mm	5000 K	satiniert	20,0 W	2922 lm
HaILED 17-1145 AS	87017503009	1145x39x64 mm	5000 K	klar	19,8 W	3220 lm
HaILED 17-1145 AS dim	87017503010	1145x39x64 mm	5000 K	klar	20,0 W	3220 lm
HaILED 22-1425 AS	87022303003	1425x39x64 mm	3000 K	satiniert	24,3 W	3340 lm
HaILED 22-1425 AS dim	87022303004	1425x39x64 mm	3000 K	satiniert	24,6 W	3340 lm
HaILED 22-1425 AS	87022303009	1425x39x64 mm	3000 K	klar	24,3 W	3681 lm
HaILED 22-1425 AS dim	87022303010	1425x39x64 mm	3000 K	klar	24,6 W	3681 lm
HaILED 22-1425 AS	87022403003	1425x39x64 mm	4000 K	satiniert	24,3 W	3604 lm
HaILED 22-1425 AS dim	87022403004	1425x39x64 mm	4000 K	satiniert	24,6 W	3604 lm
HaILED 22-1425 AS	87022403009	1425x39x64 mm	4000 K	klar	24,3 W	3972 lm
HaILED 22-1425 AS dim	87022403010	1425x39x64 mm	4000 K	klar	24,6 W	3972 lm
HaILED 22-1425 AS	87022503003	1425x39x64 mm	5000 K	satiniert	24,3 W	3648 lm
HaILED 22-1425 AS dim	87022503004	1425x39x64 mm	5000 K	satiniert	24,6 W	3648 lm
HaILED 22-1425 AS	87022503009	1425x39x64 mm	5000 K	klar	24,3 W	4021 lm
HaILED 22-1425 AS dim	87022503010	1425x39x64 mm	5000 K	klar	24,6 W	4021 lm
HaILED 24-865 AS	87024303003	865x39x64 mm	3000 K	satiniert	27,0 W	3353 lm
HaILED 24-865 AS dim	87024303004	865x39x64 mm	3000 K	satiniert	27,4 W	3353 lm
HaILED 24-865 AS	87024303009	865x39x64 mm	3000 K	klar	27,0 W	3696 lm
HaILED 24-865 AS dim	87024303010	865x39x64 mm	3000 K	klar	27,4 W	3696 lm
HaILED 24-865 AS	87024403003	865x39x64 mm	4000 K	satiniert	27,0 W	3604 lm
HaILED 24-865 AS dim	87024403004	865x39x64 mm	4000 K	satiniert	27,4 W	3604 lm
HaILED 24-865 AS	87024403009	865x39x64 mm	4000 K	klar	27,0 W	3972 lm
HaILED 24-865 AS dim	87024403010	865x39x64 mm	4000 K	klar	27,4 W	3972 lm
HaILED 24-865 AS	87024503003	865x39x64 mm	5000 K	satiniert	27,0 W	3656 lm
HaILED 24-865 AS dim	87024503004	865x39x64 mm	5000 K	satiniert	27,4 W	3656 lm
HaILED 24-865 AS	87024503009	865x39x64 mm	5000 K	klar	27,0 W	4030 lm
HaILED 24-865 AS dim	87024503010	865x39x64 mm	5000 K	klar	27,4 W	4030 lm
HaILED 30-1425 AS	87030303003	1425x39x64 mm	3000 K	satiniert	30,6 W	4092 lm
HaILED 30-1425 AS dim	87030303004	1425x39x64 mm	3000 K	satiniert	30,9 W	4092 lm
HaILED 30-1425 AS	87030303009	1425x39x64 mm	3000 K	klar	30,6 W	4511 lm
HaILED 30-1425 AS dim	87030303010	1425x39x64 mm	3000 K	klar	30,9 W	4511 lm
HaILED 30-1425 AS	87030403003	1425x39x64 mm	4000 K	satiniert	30,6 W	4400 lm
HaILED 30-1425 AS dim	87030403004	1425x39x64 mm	4000 K	satiniert	30,9 W	4400 lm
HaILED 30-1425 AS	87030403009	1425x39x64 mm	4000 K	klar	30,6 W	4850 lm
HaILED 30-1425 AS dim	87030403010	1425x39x64 mm	4000 K	klar	30,9 W	4850 lm
HaILED 30-1425 AS	87030503003	1425x39x64 mm	5000 K	satiniert	30,6 W	4484 lm
HaILED 30-1425 AS dim	87030503004	1425x39x64 mm	5000 K	satiniert	30,9 W	4484 lm
HaILED 30-1425 AS	87030503009	1425x39x64 mm	5000 K	klar	30,6 W	4942 lm
HaILED 30-1425 AS dim	87030503010	1425x39x64 mm	5000 K	klar	30,9 W	4942 lm
HaILED 32-1145 AS	87032303003	1145x39x64 mm	3000 K	satiniert	34,8 W	4470 lm
HaILED 32-1145 AS dim	87032303004	1145x39x64 mm	3000 K	satiniert	35,2 W	4470 lm
HaILED 32-1145 AS	87032303009	1145x39x64 mm	3000 K	klar	34,8 W	4928 lm
HaILED 32-1145 AS dim	87032303010	1145x39x64 mm	3000 K	klar	35,2 W	4928 lm
HaILED 32-1145 AS	87032403003	1145x39x64 mm	4000 K	satiniert	34,8 W	4822 lm
HaILED 32-1145 AS dim	87032403004	1145x39x64 mm	4000 K	satiniert	35,2 W	4822 lm
HaILED 32-1145 AS	87032403009	1145x39x64 mm	4000 K	klar	34,8 W	5316 lm
HaILED 32-1145 AS dim	87032403010	1145x39x64 mm	4000 K	klar	35,2 W	5316 lm
HaILED 32-1145 AS	87032503003	1145x39x64 mm	5000 K	satiniert	34,8 W	4893 lm
HaILED 32-1145 AS dim	87032503004	1145x39x64 mm	5000 K	satiniert	35,2 W	4893 lm
HaILED 32-1145 AS	87032503009	1145x39x64 mm	5000 K	klar	34,8 W	5393 lm
HaILED 32-1145 AS dim	87032503010	1145x39x64 mm	5000 K	klar	35,2 W	5393 lm
HaILED 40-1425 AS	87040303003	1425x39x64 mm	3000 K	satiniert	42,6 W	5588 lm
HaILED 40-1425 AS dim	87040303004	1425x39x64 mm	3000 K	satiniert	43,0 W	5588 lm
HaILED 40-1425 AS	87040303009	1425x39x64 mm	3000 K	klar	42,6 W	6160 lm
HaILED 40-1425 AS dim	87040303010	1425x39x64 mm	3000 K	klar	43,0 W	6160 lm
HaILED 40-1425 AS	87040403003	1425x39x64 mm	4000 K	satiniert	42,6 W	6024 lm
HaILED 40-1425 AS dim	87040403004	1425x39x64 mm	4000 K	satiniert	43,0 W	6024 lm
HaILED 40-1425 AS	87040403009	1425x39x64 mm	4000 K	klar	42,6 W	6640 lm
HaILED 40-1425 AS dim	87040403010	1425x39x64 mm	4000 K	klar	43,0 W	6640 lm
HaILED 40-1425 AS	87040503003	1425x39x64 mm	5000 K	satiniert	42,6 W	6112 lm
HaILED 40-1425 AS dim	87040503004	1425x39x64 mm	5000 K	satiniert	43,0 W	6112 lm
HaILED 40-1425 AS	87040503009	1425x39x64 mm	5000 K	klar	42,6 W	6737 lm
HaILED 40-1425 AS dim	87040503010	1425x39x64 mm	5000 K	klar	43,0 W	6737 lm