

Bezeichnung	Artikelnummer	Lichtfarbe	Optik	System-leistung	Lichtstrom System	Abmessungen
HalLED 16-865 AS	87016303003	3000 K	satiniert	15,0 W	2138 lm	865x39x64 mm
HalLED 16-865 AS dim	87016303004	3000 K	satiniert	15,2 W	2138 lm	865x39x64 mm
HalLED 16-865 AS	87016303009	3000 K	klar	15,0 W	2357 lm	865x39x64 mm
HalLED 16-865 AS dim	87016303010	3000 K	klar	15,2 W	2357 lm	865x39x64 mm
HalLED 16-865 AS	87016403003	4000 K	satiniert	15,0 W	2270 lm	865x39x64 mm
HalLED 16-865 AS dim	87016403004	4000 K	satiniert	15,2 W	2270 lm	865x39x64 mm
HalLED 16-865 AS	87016403009	4000 K	klar	15,0 W	2503 lm	865x39x64 mm
HalLED 16-865 AS dim	87016403010	4000 K	klar	15,2 W	2503 lm	865x39x64 mm
HalLED 16-865 AS dim	87016503004	5000 K	satiniert	15,2 W	2270 lm	865x39x64 mm
HalLED 16-865 AS	87016503009	5000 K	klar	15,0 W	2503 lm	865x39x64 mm
HalLED 16-865 AS dim	87016503010	5000 K	klar	15,2 W	2503 lm	865x39x64 mm
HalLED 17-1145 AS	87017303003	3000 K	satiniert	19,4 W	2851 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017303004	3000 K	satiniert	19,7 W	2851 lm	1145x39x64 mm
HalLED 17-1145 AS	87017303009	3000 K	klar	19,4 W	3143 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017303010	3000 K	klar	19,7 W	3143 lm	1145x39x64 mm
HalLED 17-1145 AS	87017403003	4000 K	satiniert	19,4 W	3027 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017403004	4000 K	satiniert	19,7 W	3027 lm	1145x39x64 mm
HalLED 17-1145 AS	87017403009	4000 K	klar	19,4 W	3337 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017403010	4000 K	klar	19,7 W	3337 lm	1145x39x64 mm
HalLED 17-1145 AS	87017503003	5000 K	satiniert	19,4 W	3027 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017503004	5000 K	satiniert	19,7 W	3027 lm	1145x39x64 mm
HalLED 17-1145 AS	87017503009	5000 K	klar	19,4 W	3337 lm	1145x39x64 mm
HalLED 17-1145 AS dim	87017503010	5000 K	klar	19,7 W	3337 lm	1145x39x64 mm
HalLED 22-1425 AS	87022303003	3000 K	satiniert	23,9 W	3564 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022303004	3000 K	satiniert	24,2 W	3564 lm	1425x39x64 mm
HalLED 22-1425 AS	87022303009	3000 K	klar	23,9 W	3929 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022303010	3000 K	klar	24,2 W	3929 lm	1425x39x64 mm
HalLED 22-1425 AS	87022403003	4000 K	satiniert	23,9 W	3784 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022403004	4000 K	satiniert	24,2 W	3784 lm	1425x39x64 mm
HalLED 22-1425 AS	87022403009	4000 K	klar	23,9 W	4171 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022403010	4000 K	klar	24,2 W	4171 lm	1425x39x64 mm
HalLED 22-1425 AS	87022503003	5000 K	satiniert	23,9 W	3784 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022503004	5000 K	satiniert	24,2 W	3784 lm	1425x39x64 mm
HalLED 22-1425 AS	87022503009	5000 K	klar	23,9 W	4171 lm	1425x39x64 mm
HalLED 22-1425 AS dim	87022503010	5000 K	klar	24,2 W	4171 lm	1425x39x64 mm
HalLED 24-865 AS	87024303003	3000 K	satiniert	26,9 W	3630 lm	865x39x64 mm
HalLED 24-865 AS dim	87024303004	3000 K	satiniert	27,2 W	3630 lm	865x39x64 mm
HalLED 24-865 AS	87024303009	3000 K	klar	26,9 W	4001 lm	865x39x64 mm
HalLED 24-865 AS dim	87024303010	3000 K	klar	27,2 W	4001 lm	865x39x64 mm
HalLED 24-865 AS	87024403003	4000 K	satiniert	26,9 W	3868 lm	865x39x64 mm
HalLED 24-865 AS dim	87024403004	4000 K	satiniert	27,2 W	3868 lm	865x39x64 mm
HalLED 24-865 AS	87024403009	4000 K	klar	26,9 W	4263 lm	865x39x64 mm
HalLED 24-865 AS dim	87024403010	4000 K	klar	27,2 W	4263 lm	865x39x64 mm
HalLED 24-865 AS	87024503003	5000 K	satiniert	26,9 W	3868 lm	865x39x64 mm

HalLED 24-865 AS dim	87024503004	5000 K	satiniert	27,2 W	3868 lm	865x39x64 mm
HalLED 24-865 AS	87024503009	5000 K	klar	26,9 W	4263 lm	865x39x64 mm
HalLED 24-865 AS dim	87024503010	5000 K	klar	27,2 W	4263 lm	865x39x64 mm
HalLED 30-1425 AS	87030303003	3000 K	satiniert	30,4 W	4400 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030303004	3000 K	satiniert	30,7 W	4400 lm	1425x39x64 mm
HalLED 30-1425 AS	87030303009	3000 K	klar	30,4 W	4850 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030303010	3000 K	klar	30,7 W	4850 lm	1425x39x64 mm
HalLED 30-1425 AS	87030403003	4000 K	satiniert	30,4 W	4686 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030403004	4000 K	satiniert	30,7 W	4686 lm	1425x39x64 mm
HalLED 30-1425 AS	87030403009	4000 K	klar	30,4 W	5165 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030403010	4000 K	klar	30,7 W	5165 lm	1425x39x64 mm
HalLED 30-1425 AS	87030503003	5000 K	satiniert	30,4 W	4686 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030503004	5000 K	satiniert	30,7 W	4686 lm	1425x39x64 mm
HalLED 30-1425 AS	87030503009	5000 K	klar	30,4 W	5165 lm	1425x39x64 mm
HalLED 30-1425 AS dim	87030503010	5000 K	klar	30,7 W	5165 lm	1425x39x64 mm
HalLED 32-1145 AS	87032303003	3000 K	satiniert	34,7 W	4840 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032303004	3000 K	satiniert	35,1 W	4840 lm	1145x39x64 mm
HalLED 32-1145 AS	87032303009	3000 K	klar	34,7 W	5335 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032303010	3000 K	klar	35,1 W	5335 lm	1145x39x64 mm
HalLED 32-1145 AS	87032403003	4000 K	satiniert	34,7 W	5157 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032403004	4000 K	satiniert	35,1 W	5157 lm	1145x39x64 mm
HalLED 32-1145 AS	87032403009	4000 K	klar	34,7 W	5684 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032403010	4000 K	klar	35,1 W	5684 lm	1145x39x64 mm
HalLED 32-1145 AS	87032503003	5000 K	satiniert	34,7 W	5157 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032503004	5000 K	satiniert	35,1 W	5157 lm	1145x39x64 mm
HalLED 32-1145 AS	87032503009	5000 K	klar	34,7 W	5684 lm	1145x39x64 mm
HalLED 32-1145 AS dim	87032503010	5000 K	klar	35,1 W	5684 lm	1145x39x64 mm
HalLED 40-1425 AS	87040303003	3000 K	satiniert	42,5 W	6050 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040303004	3000 K	satiniert	42,9 W	6050 lm	1425x39x64 mm
HalLED 40-1425 AS	87040303009	3000 K	klar	42,5 W	6669 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040303010	3000 K	klar	42,9 W	6669 lm	1425x39x64 mm
HalLED 40-1425 AS	87040403003	4000 K	satiniert	42,5 W	6446 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040403004	4000 K	satiniert	42,9 W	6446 lm	1425x39x64 mm
HalLED 40-1425 AS	87040403009	4000 K	klar	42,5 W	7105 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040403010	4000 K	klar	42,9 W	7105 lm	1425x39x64 mm
HalLED 40-1425 AS	87040503003	5000 K	satiniert	42,5 W	6446 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040503004	5000 K	satiniert	42,9 W	6446 lm	1425x39x64 mm
HalLED 40-1425 AS	87040503009	5000 K	klar	42,5 W	7105 lm	1425x39x64 mm
HalLED 40-1425 AS dim	87040503010	5000 K	klar	42,9 W	7105 lm	1425x39x64 mm